

CF2USAT18E

1.8" Micro SATA to Compact Flash Solid State Drive Enclosure Adapter

Installation Guide

Packaging Contents

- 1 x CF2USAT18E enclosure
- 1 x Mini Screwdrivers
- 1 x Installation Guide

System Requirements

- 3.3V Compact Flash card
- Microsoft Windows® 2000/XP/Vista, Mac OS® 10.x, Linux®

Installation Hardware Installation

1. Remove the 4 small screws on the underside of the enclosure, and remove the cover plate.
2. Remove the circuit board and insert the Compact Flash card into the CF card slot.
3. Reinstall the circuit board into the enclosure.
4. Place the metal cover back on and replace the 4 screws.

Driver Installation

No drivers should need to be installed for this enclosure, as the enclosure appears as a standard SATA hard drive.

Warranty Information

This product is backed by a one year warranty.

In addition, StarTech.com warrants its products against defects in materials

and workmanship for the periods noted, following the initial date of purchase. During this period, the products may be returned for repair, or replacement with equivalent products at our discretion. The warranty covers parts and labor costs only. StarTech.com does not warrant its products from defects or damages arising from misuse, abuse, alteration, or normal wear and tear.

Limitation of Liability

In no event shall the liability of StarTech.com Ltd. and StarTech.com USA LLP (or their officers, directors, employees or agents) for any damages (whether direct or indirect, special, punitive, incidental, consequential, or otherwise), loss of profits, loss of business, or any pecuniary loss, arising out of or related to the use of the product exceed the actual price paid for the product. Some states do not allow the exclusion or limitation of incidental or consequential damages. If such laws apply, the limitations or exclusions contained in this statement may not apply to you.

StarTech.com

Making hard-to-find easy!®

Specifications

Bus Interface	SATA rev 2.x
Connectors	Micro SATA connector (7+9 pin)
Power Consumption	5V / 150mA
CF Compatibility	3.3V CF type I and II (SLC/MLC)*
Supported Operating Systems	Windows® 2000/XP/Vista, Mac OS® 10.x, Linux®

* Note: If an MLC type card is used, write speeds will be less than